

Assembly and **Installation Instructions** for Model's

30064FM

Warning please make sure the electrical breaker is shut off before commencing with this installation

Package Contents		
Part	Description	Qty
Α	Mounting bracket	1
В	Mounting bracket screws	2
С	Electrical connectors	3
D	Fixture assembly	1
E	Ceiling anchor	1
F	Anchor screw	1
G	Threaded bolts	2
Н	Glass diffuser	1
I	Mounting knobs	3
J	Diffuser assembly	1

Installing the fixture
please ensure the electrical breaker is in
the Off position before commencing

- Loosely attach the Mounting bracket (A) to the Junction box and mark where the three Ceiling anchor (E) will be placed. Remove the Mounting bracket (A) and secure the Ceiling anchor (E) into their marked spot on the ceiling.
- Attach the Mounting bracket to the Junction box using the Mounting bracket screws (B) provided. Secure to the ceiling by screwing the Anchor screw (F) inot the Anchor (E).
 - Connect the supply wires to the fixture wires using the supplied electrical wire connectors (C). White supply wire to the White fixture wire, Black supply wire to Black fixture wire and the ground Bare Copper or Green wire to the Green fixture wire. Once the electrical wire connectors are securely fastened it is recommended to tape these connectors with electrical tape.
- Secure the Fixture assembly (D) onto the Mounting bracket (A) using the Threaded bolts (G) provided.
- Insert the Glass diffuser (H) into the Diffuser assembly (J) and secure in place with the Mounting knobs (1).
- Attach the Diffuser assembly (J) to the Canopy (D) by inserting the Mounting knobs (I) through the openings on the Fixtue assembly and twist to lock into position.
- Switch on the electrical breaker switch and your new fixture is ready for many years of trouble free use.

CAUTION - RISK OF FIRE

Installation of this fixture should be done by a licensed electrician or by a person familiar with local electrical codes and the construction and operation of this fixture.



