

Assembly and Installation Instructions for Model's

30069-70FM

Warning please make sure the electrical breaker is shut off before commencing with this installation

CAUTION - RISK OF FIRE

Installation of this fixture should be done by a licensed electrician or by a person familiar with local electrical codes and the construction and operation of this fixture.

Package Contents		
Part	Description	Qty
A	Mounting plate with threaded studs	1
B	Mounting plate screws	2
C	Fixture assembly	1
D	Electrical connectors	3
E	Canopy	1
F	Fixture mounting nuts	2

Installing the fixture *please ensure the electrical breaker is switched off before commencing*

- Attach the supplied Mounting plate **(A)** with the Mounting studs are facing away from the Junction-Box. And secure in place with the two supplied Mounting plate screws **(B)**.
- Connect the supply wires to the fixture wires using the supplied electrical wire connectors **(D)**. White supply wire to the White fixture wire, Black supply wire to Black fixture wire and the ground Bare Copper or Green wire to the Green fixture wire. Once the electrical wire connectors are securely fastened it is recommended to tape these connectors with electrical tape.
- Attach the Fixture assembly **(C)** to the Mounting plate **(A)** by inserting the Threaded studs through the holes provided on the Fixture assembly and secure with the supplied Fixture mounting nuts **(E)**.
- Place the Thin white diffuser and Thick clear diffusers onto the LED cluster and then secure in place with the two Allan screws.
- Switch on the electrical breaker switch and your new fixture is ready for many years of trouble free use

